

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
8 December 2005 (08.12.2005)

PCT

(10) International Publication Number
WO 2005/115574 A1

(51) International Patent Classification⁷: **A63F 9/12**

(21) International Application Number:
PCT/KR2005/001509

(22) International Filing Date: 23 May 2005 (23.05.2005)

(25) Filing Language: Korean

(26) Publication Language: English

(30) Priority Data:
10-2004-0037781 27 May 2004 (27.05.2004) KR

(71) Applicant and

(72) Inventor: LEE, Ki-Tae [KR/KR]; #201, 113-4, Seongsan
1-dong, Mapo-gu, Seoul 121-251 (KR).

(74) Agent: KIM, Chong-Hwa; 2F., Shindo Bldg., 823-10,
Yeoksam-dong, Kangnam-gu, Seoul 135-080 (KR).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,

AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KM, KP, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NG, NI, NO, NZ, OM,
PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM,
SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN,
YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,
SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN,
GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: THE SOLID PUZZLE BLOCK



(57) Abstract: Provided is a solid puzzle block (1). The solid puzzle block has a connecting groove (13 and 33) open from the top to the bottom of a side surface (11 and 31) of its main body to allow cross-connecting of two blocks, and a connecting peg (14) and connecting hole (15) formed at either end of the connecting groove (13) on the side surface (11 and 31) to allow side-connecting of two blocks. In order to impart a firm cross-connection, a plurality of embossings (12) are formed on the left and right surfaces of the connecting groove (13 and 33) and the contact portions (42) of the upper and lower surfaces (40 and 41) contacting the connecting groove (13 and 33). At an end surface (16 and 36) between the left and right surfaces of the connecting groove (13 and 33) is fixed a connector (17), to which an operating unit (21) located inside the main body is connected electrically. Although the firmly connecting block is not of an assorted variety, it can arouse enjoyment and curiosity in users of all ages.

WO 2005/115574 A1